

**FLOOD DAMAGE PREVENTION ORDINANCE**  
MORGAN COUNTY, ALABAMA

**ARTICLE 1**

**STATUTORY AUTHORIZATION, FINDING OF FACT, PURPOSE AND OBJECTIVES**

**SECTION A.           STATUTORY AUTHORIZATION**

The Legislature of the State of Alabama has in Title 11, Chapter 19, Sections 1-24, Chapter 24, Sections 1-7, Chapter 52, Section 30, and Title 41, Chapter 9, Section 166 of the Code of Alabama, 1975, authorized local government units to adopt regulations designed to promote the public health, safety, and general welfare of its citizenry. Therefore, the Morgan County Commission, of Morgan County, Alabama, does ordain as follows:

**SECTION B.           FINDINGS OF FACT**

The flood hazard areas of Morgan County, Alabama are subject to periodic inundation which results in loss of life and property, health and safety hazards, disruption of commerce and governmental services, extraordinary public expenditures for flood relief and protection, and impairment of the tax base, all of which adversely affect the public health, safety and general welfare.

These flood losses are caused by the occupancy in flood hazard areas of uses vulnerable to floods, which are inadequately elevated, flood proofed, or otherwise unprotected from flood damages, and by the cumulative effect of obstructions in floodplains causing increases in flood heights and velocities.

**SECTION C.           STATEMENT OF PURPOSE**

It is the purpose of this ordinance to promote the public health, safety and general welfare and to minimize public and private losses due to flood conditions in specific areas by provisions designed to:

- (1) require that uses vulnerable to floods, including facilities which serve such uses, be protected against flood damage at the time of initial construction;
- (2) restrict or prohibit uses which are dangerous to health, safety and property due to water or erosion hazards, or which increase flood heights, velocities, or erosion;
- (3) control filling, grading, dredging and other development which may increase flood damage or erosion;
- (4) prevent or regulate the construction of flood barriers which will unnaturally divert flood waters or which may increase flood hazards to other lands; and
- (5) control the alteration of natural floodplains, stream channels, and natural protective barriers which are involved in the accommodation of flood waters.

**SECTION D.           OBJECTIVES**

The objectives of this ordinance are:

- (1) to protect human life and health;

- (2) to minimize damage to public facilities and utilities such as water and gas mains, electric, telephone and sewer lines, streets and bridges located in floodplains;
- (3) to help maintain a stable tax base by providing for the sound use and development of flood prone areas in such a manner as to minimize flood blight areas,
- (4) to minimize expenditure of public money for costly flood control projects;
- (5) to minimize the need for rescue and relief efforts associated with flooding and generally undertaken at the expense of the general public;
- (6) to minimize prolonged business interruptions, and
- (7) to provide a resource for potential home buyers to determine if property is in a designated flood area.

**ARTICLE 2**  
**GENERAL PROVISIONS**

**SECTION A.           LANDS TO WHICH THIS ORDINANCE APPLIES**

This ordinance shall apply to all Areas of Special Flood Hazard within the jurisdiction of Morgan County, Alabama, also referred to herein as the “Community”.

**SECTION B.           BASIS FOR AREA OF SPECIAL FLOOD HAZARD**

The Areas of Special Flood Hazard identified by the Federal Emergency Management Agency in its **Flood Insurance Study (FIS), dated August 16, 2018**, with accompanying maps and other supporting data **and any revision thereto**, are adopted by reference and declared a part of this ordinance. Areas of Special Flood Hazard may also include those areas known to have flooded historically or defined through standard engineering analysis by governmental agencies or private parties but not yet incorporated in the FIS.

When Preliminary Flood Insurance Studies and Flood Insurance Rate Maps have been provided by FEMA to Morgan County:

- (1) Prior to the issuance of a Letter of Final Determination (LFD) by FEMA, the use of the preliminary flood hazard data shall only be required where no base flood elevations and/or floodway areas exist or where the preliminary base flood elevations or floodway area exceed the base flood elevations and/or floodway widths in the effective flood hazard data provided by FEMA. Such preliminary data may be subject to revision through valid appeals.
- (2) Upon the issuance of a Letter of Final Determination (LFD) by FEMA, the revised flood hazard data shall be used and replace all previously effective flood hazard data provided by FEMA for the purposes of administrating these regulations.

Where adopted regulatory standards conflict, the more stringent base flood elevation shall prevail. Preliminary FIS data may be subject to change by a valid appeal.

**SECTION C. ESTABLISHMENT OF A FLOODPLAIN DEVELOPMENT PERMIT**

A Development Permit shall be required in conformance with the provisions of this ordinance PRIOR to the commencement of any development activities in identified areas of special flood hazard and community flood hazard areas within Morgan County, Alabama.

**SECTION D. COMPLIANCE**

No structure or land shall hereafter be located, extended, converted or altered without full compliance with the terms of this ordinance and other applicable regulations.

**SECTION E. ABROGATION AND GREATER RESTRICTIONS**

This ordinance is not intended to repeal, abrogate, or impair any existing ordinance, easements, covenants, or deed restrictions. However, where this ordinance and another conflict or overlap, whichever imposes the more stringent restrictions shall prevail. This Ordinance supersedes and replaces the “FLOOD DAMAGE PREVENTION ORDINANCE For MORGAN COUNTY, ALABAMA” adopted by the Morgan County Commission on February 25, 1991 and January 28, 2002.

**SECTION F. INTERPRETATION**

In the interpretation and application of this ordinance, all provisions shall be:

- (1) considered as minimum requirements.
- (2) liberally construed in favor of the governing body.
- (3) deemed neither to limit nor repeal any other powers granted under state statutes.

**SECTION G. WARNING AND DISCLAIMER OF LIABILITY**

The degree of flood protection required by this ordinance is considered reasonable for regulatory purposes and is based on scientific and engineering considerations. Larger floods can and will occur; flood heights may be increased by man-made or natural causes. This ordinance does not imply that land outside the Areas of Special Flood Hazard or uses permitted within such areas will be free from flooding or flood damages. This ordinance shall not create liability on the part of Morgan County, the Morgan County Commission, the Morgan County Engineer, the Floodplain Administrator or by any officer or employee thereof for any flood damages that result from reliance on this ordinance or any administrative decision lawfully made thereunder.

**SECTION H. PENALTIES FOR VIOLATION**

- (1) Notice of Violation. If Morgan County determines that an owner, applicant or other responsible person has failed to comply with the terms and conditions of a permit, or the provisions of this ordinance, it shall issue a written notice of violation, by certified return receipt mail, to such applicant or other responsible person. Where the person is engaged in activity covered by this ordinance without having first secured a permit, the notice shall be served on the owner, applicant or the responsible person in charge of the activity being conducted on the site. The notice of violation shall contain:
  - (a) The name and address of the owner, applicant or the responsible person;
  - (b) The address or other description of the site upon which the violation is occurring;
  - (c) A statement specifying the nature of the violation;

- (d) A description of the remedial measures necessary to bring the action or inaction into compliance with the permit or this ordinance and the date for the completion of such remedial action;
  - (e) A statement of the penalty or penalties that may be assessed against the person to whom the notice of violation is directed, and;
- (2) Additional Enforcement Actions. If the remedial measures described in the Notice of Violation have not been completed by the date set forth for such completion in the Notice of Violation, any one or more of the following enforcement actions may be enacted against the person to whom the Notice of Violation was directed. Before taking any of the following actions or imposing any of the following penalties, the Community shall first notify the applicant or other responsible person in writing of its intended action. The Community shall provide reasonable opportunity, of not less than ten days (except, that in the event the violation constitutes an immediate danger to public health or public safety, 24-hour notice shall be sufficient) to cure such violation. In the event the applicant or other responsible person fails to cure such violation after such notice and cure period, the Community may take or impose any one or more of the following enforcement actions or penalties:
- (a) Stop Work Order: The Community may issue a stop work order, which shall be served on the applicant or other responsible person. The stop work order shall remain in effect until the applicant or other responsible person has taken the remedial measures set forth in the notice of violation or has otherwise cured the violation or violations described therein. The stop work order may be withdrawn or modified to enable the applicant or other responsible person to take the necessary remedial measures to cure such violation or violations.
  - (b) Suspension, revocation, or modifications of permit: The Community may suspend, revoke, or modify the permit authorizing the development project. A suspended, revoked, or modified permit may be reinstated after the applicant or other responsible person has taken the remedial measures set forth in the notice of violation or has otherwise cured the violations described therein, provided such permit may be reinstated (upon such conditions as the Community may deem necessary) to enable the applicant or other responsible person to take the necessary remedial measures to cure such violations.
  - (c) Civil penalties: Violation of the provisions of this ordinance or failure to comply with any of its requirements, including violation of conditions and safeguards established in connection with grants of variance or special exceptions shall constitute a misdemeanor. Any person, firm, corporation or agency who violates this ordinance, fails to obtain the permit required herein or who violates any provision of this ordinance, shall be guilty of a misdemeanor and, upon conviction, may be fined not more than \$500.00, or may be imprisoned in the county jail for not more than one year or may be both fined and imprisoned, and in addition, shall pay all costs and expenses involved in the case: Each day such violation continues shall be considered a separate offense. Nothing herein contained shall prevent Morgan County from taking such other lawful actions as is necessary to prevent or remedy any violation.
  - (d) Section 1316 Declaration: Section 1316 of the National Flood Insurance Act authorizes FEMA to deny flood insurance to a property declared by the State, County, or Municipal government to be in violation of the local floodplain management ordinance. A Section 1316 declaration shall be used when all other legal means to remedy a violation have been exhausted and the structure is noncompliant. Once invoked, the property's flood insurance coverage will be terminated and no new or renewal policy can be issued; no flood insurance claim can be paid on any policy on the property, and disaster assistance

will be denied.

The declaration must be in writing (letter or citation), from the Community to the property owner and the applicable FEMA Regional Office, and must contain the following items:

- (i) The name(s) of the property owner(s) and address or legal description of the property sufficient to confirm its identity and location;
- (ii) A clear and unequivocal declaration that the property is in violation of a cited State or local law, regulation or ordinance;
- (iii) A clear statement that the public body making the declaration has authority to do so and a citation to that authority;
- (iv) Evidence that the property owner has been provided notice of the violation and the prospective denial of insurance; and
- (v) A clear statement that the declaration is being submitted pursuant to section 1316 of the National Flood Insurance Act of 1968, as amended.

If a structure that has received a Section 1316 declaration is made compliant with the Community's floodplain management ordinance, then the Section 1316 declaration can be rescinded by the community and flood insurance eligibility restored.

- (3) Administrative appeal; judicial review. Any person receiving a Notice of Violation may appeal the determination of the Community, including but not limited to the issuance of a stop work order, the assessment of an administratively-imposed monetary penalty, the suspension, revocation, modification, or grant with condition of a permit by the Community upon finding that the holder is in violation of permit conditions, or that the holder is in violation of any applicable ordinance or any of the Community's rules and regulations, or the issuance of a notice of bond forfeiture.

The Notice of Appeal must be in writing and must be received within ten (10) days from the date of the Notice of Violation. A hearing on the appeal shall take place within thirty (30) days from the date of receipt of the Notice of Appeal by the Floodplain Administrator.

- (4) All appeals shall be heard and decided by the Community's designated Appeal Board, which shall be the Morgan County Commission, or their designees. The Appeal Board shall have the power to affirm, modify, or reject the original penalty, including the right to increase or decrease the amount of any monetary penalty and the right to add or delete remedial actions required for correction of the violation and compliance with the Community's flood damage prevention ordinance, and any other applicable local, state, or federal requirements. The decision of the Appeal Board shall be final.
- (5) A judicial review can be requested by any person aggrieved by a decision or order of the Community, after exhausting his/her administrative remedies. They shall have the right to appeal de novo to the Morgan County Circuit Court.

## **SECTION I. SAVINGS CLAUSE**

If any section, subsection, sentence, clause, phrase, or word of this ordinance is for any reason held to be noncompliant with Title 11, Chapter 19, Chapter 24, Chapter 52, Code of Alabama, 1975 or 44 Code of Federal Regulation 59-78, or other relevant State and Federal Code Sections, such decision shall not affect the validity of the remaining portions of this ordinance.

**ARTICLE 3**  
**ADMINISTRATION**

**SECTION A.           DESIGNATION OF FLOODPLAIN ADMINISTRATOR**

The **Morgan County Engineer**, also referred herein to as the Floodplain Administrator, is hereby appointed to administer and implement the provisions of this ordinance. The Floodplain Administrator shall have the authority to designate staff and other employees to assist in the administration and implementation of the provisions of this ordinance.

**SECTION B.           PERMIT PROCEDURES**

Application for permit to develop in a special flood hazard area shall be made to the Floodplain Administrator on forms furnished by the Community **PRIOR** to any development activities, and may include, but not be limited to, the following: Plans in duplicate drawn to scale showing the elevations of the area in question and the nature, location, dimensions, of existing or proposed structures, fill placement, storage of materials or equipment, and drainage facilities.

Specifically, the following information is required:

(1) Application Stage

- (a) A completed Application For Permit To Develop In A Special Flood Hazard Area.
- (b) Elevation in relation to mean sea level (or highest adjacent grade) of the regulatory lowest floor level, including basement, of all proposed structures; an appropriate FEMA Elevation Certificate is required for each structure.
- (c) Elevation in relation to mean sea level to which any non-residential structure will be flood proofed.
- (d) Design certification from a registered professional engineer or architect that any proposed non-residential flood-proofed structure will meet the flood-proofing criteria of Article 4, Sections B(2) and E(2).
- (e) Description of the extent to which any watercourse will be altered or relocated as a result of a proposed development. Design certification from a registered professional engineer **THAT** assures flood carrying capacity of any altered or relocated watercourse is maintained.
- (f) Design certification and plans by a registered professional engineer or architect for proposed foundations that meet the criteria of Article 4, Sections B(3) & B(4). A registered professional engineer or architect shall certify that the building and foundation systems are designed and adequately anchored to resist buoyancy, flotation, collapse, and lateral movement resulting from hydrodynamic and hydrostatic loads. Design shall be in accordance with the Base Flood Elevation (BFE), velocities, and other criteria as described and located in the Flood Insurance Study (FIS) and the Flood Insurance Rate Map (FIRM), Morgan County, Alabama.
- (g) Design certification from a registered professional engineer that any proposed development within a designated floodway shall meet the criteria of Article 4, Section C and D(3). A “No-Rise / No Impact” certification shall be required.

(2) Construction Stage

For all new construction and substantial improvements, the permit holder shall provide to the Floodplain Administrator an as-built certification of the regulatory floor elevation or flood-

proofing level using appropriate FEMA Elevation or Floodproofing Certificate, immediately after the lowest floor or flood proofing is completed. When flood proofing is utilized for non-residential structures, said certification shall be prepared by or under the direct supervision of a professional engineer or architect and certified by same.

Any work undertaken prior to submission of these certifications are considered a violation and shall be at the permit holder's risk. The Floodplain Administrator shall review the above referenced certification data submitted. Deficiencies detected by such review shall be corrected by the permit holder immediately and prior to further progressive work being allowed to proceed. Failure to submit certifications or failure to make said corrections required hereby, shall be cause to issue a stop-work order for the project.

(3) Finished Construction

Upon completion of construction, for all new construction and substantial improvements, the permit holder shall provide to the Floodplain Administrator the following:

- (a) An appropriate FEMA Elevation Certificate which depicts all finished construction elevations for each structure.
- (b) As-Built Certification from a registered professional engineer or architect that the design and methods of finished construction is in accordance with accepted standards of practice for construction that require designs as set forth in Article 3, Section B(1)(f) and Article 4, Sections B(3) & B(4).
- (c) When flood proofing is utilized for non-residential structures, an appropriate FEMA Floodproofing Certificate which depicts all finished construction and flood-proofing criteria of Article 4, Sections B(2) and E(2) is required to be submitted to the Floodplain Administrator for each structure.

**SECTION C. DUTIES AND RESPONSIBILITIES OF THE ADMINISTRATOR**

In the performance of the duties and responsibilities, the Floodplain Administrator has the right to require, rely on, and utilize data submitted by the applicant's Registered Professional Engineer, Land surveyor, or Architect. Duties of the Floodplain Administrator shall include, but shall not be limited to:

- (1) Review all development permits to assure that the permit requirements of this ordinance have been satisfied; and assure that development sites are reasonably safe from flooding.
- (2) Review copies of all necessary permits from governmental agencies from which approval is required by Federal or State law, including section 404 of the Federal Water Pollution Control Act Amendments of 1972, 33 U.S.C. 1334. Maintain such permits permanently with floodplain development permit file.
- (3) When Base Flood Elevation data or floodway data have not been provided in accordance with Article 2, Section B then the Floodplain Administrator shall obtain, review and reasonably utilize any base flood elevation and floodway data available from a Federal, State, or other sources in order to administer the provisions of Article 4.
- (4) Verify and record the actual elevation in relation to mean sea level (or highest adjacent grade) of the regulatory floor level, including basement, of all new construction or substantially improved structures in accordance with Article 3, Section B.

- (5) Verify and record the actual elevation, in relation to mean sea level to which any new or substantially improved structures have been flood-proofed, in accordance with Article 3, Section B and Article 4, Sections B(2) and E(2).
- (6) When flood proofing is utilized for a structure, the Floodplain Administrator shall obtain certification of design criteria from a registered professional engineer or architect in accordance with Article 3, Section B and Article 4, Section B(2) or E(2).
- (7) Notify adjacent communities and the Alabama Department of Natural Resources prior to any alteration or relocation of a watercourse and submit evidence of such notification to the Federal Emergency Management Agency (FEMA), and the Alabama Department of Economic and Community Affairs/Office of Water Resources/NFIP State Coordinator's Office.
- (8) For any altered or relocated watercourse, submit engineering data/analysis within six (6) months to FEMA and State to ensure accuracy of community flood maps through the Letter of Map Revision process. Assure flood carrying capacity of any altered or relocated watercourse is maintained. This shall be required prior to any development so as defined in Article 6. All engineering data/analysis shall be submitted by a registered professional engineer.
- (9) Where interpretation is needed as to the exact location of boundaries of the Areas of Special Flood Hazard (for example, where there appears to be a conflict between a mapped boundary and actual field conditions) the Floodplain Administrator shall make the necessary interpretation. Any person contesting the location of the boundary shall be given a reasonable opportunity to appeal the interpretation as provided in this Ordinance.
- (10) The Floodplain Administrator has the right to rely on, and utilize FEMA Technical Bulletins, along with any applicable updates, to enforce the provisions of this ordinance.
- (11) All records pertaining to the provisions of this ordinance shall be maintained in the office of the Floodplain Administrator and shall be open for public inspection.
- (12) In addition, the Floodplain Administrator and their designated staff is hereby authorized and directed to enforce the provisions of this ordinance. The Floodplain Administrator is further authorized to render interpretations of this ordinance, which are consistent with its spirit and purpose.
  - (a) Right of Entry
    - (i) Whenever necessary to make an inspection to enforce any of the provisions of this ordinance, or whenever the Floodplain Administrator or their designated staff has reasonable cause to believe that there exists in any building or upon any premises any condition or ordinance violation which makes such building, structure or premises unsafe, dangerous or hazardous, the Floodplain Administrator or their designated staff may enter such building, structure or premises at all reasonable times to inspect the same or perform any duty imposed upon the Floodplain Administrator by this ordinance.
    - (ii) If such building or premises are occupied, the Floodplain Administrator or their designated staff shall first present proper credentials and request entry. If such building, structure, or premises are unoccupied, he shall first make a reasonable effort to locate the owner or other persons having charge or control of such building or premises.
    - (iii) If entry is refused, the Floodplain Administrator shall have recourse to every remedy provided by law to secure entry.



- (iv) When the Floodplain Administrator shall have first obtained a proper inspection warrant or other remedy provided by law to secure entry, no owner or occupant or any other persons having charge, care or control of any building, structure, or premises shall fail or neglect, after proper request is made as herein provided, to promptly permit entry therein by the Floodplain Administrator or their designated staff for the purpose of inspection and examination pursuant to this ordinance.
- (b) Stop Work Orders
  - (i) Upon notice from the Floodplain Administrator, work on any building, structure or premises that is being performed contrary to the provisions of this ordinance shall immediately cease.
  - (ii) Such notice shall be in writing and shall be given to the owner of the property, or to his or her agent, or to the person doing the work, and shall state the conditions under which work may be resumed.
- (c) Revocation of Permits
  - (i) The Floodplain Administrator may revoke a permit or approval, issued under the provisions of this ordinance, in case there has been any false statement or misrepresentation as to the material fact in the application or plans on which the permit or approval was based.
  - (ii) The Floodplain Administrator may revoke a permit upon determination that the construction, erection, alteration, repair, moving, demolition, installation, or replacement of the structure for which the permit was issued is in violation of, or not in conformity with, the provisions of this ordinance.

## **ARTICLE 4**

### **PROVISIONS FOR FLOOD HAZARD REDUCTION**

#### **SECTION A.       GENERAL STANDARDS**

In ALL Areas of Special Flood Hazard the following provisions are required:

- (1) Copies of all necessary permits from governmental agencies from which approval is required by Federal or State law, including section 404 of the Federal Water Pollution Control Act Amendments of 1972, 33 U.S.C. 1334. Maintain such permits be on file.
- (2) New construction and substantial improvements of existing structures shall be anchored to prevent flotation, collapse and lateral movement of the structure.
- (3) New construction and substantial improvements of existing structures shall be constructed with materials and utility equipment resistant to flood damage.
- (4) New construction and substantial improvements of existing structures shall be constructed by methods and practices that minimize flood damage.
- (5) All subdivision proposals shall:
  - (a) be consistent with the need to minimize flood damage;
  - (b) have public utilities and facilities such as sewer, gas, electrical and water systems located and constructed to minimize flood damage;
  - (c) have adequate drainage provided to reduce exposure to flood hazards.

- (6) All heating and air conditioning equipment and components, all electrical, ventilation, plumbing, and other service facilities shall be designed and/or located to prevent water from entering or accumulating within the components during conditions of flooding.
- (7) Manufactured homes shall be anchored to prevent flotation, collapse, and lateral movement. Methods of anchoring may include, but are not limited to, use of over-the-top or frame ties to ground anchors. This standard shall be in addition to and consistent with applicable State requirements for resisting wind forces.
- (8) New and replacement water supply systems shall be designed to minimize or eliminate infiltration of flood waters into the system.
- (9) New and replacement sanitary sewage systems shall be designed to minimize or eliminate infiltration of flood waters into the systems and discharges from the systems into flood waters.
- (10) On-site waste disposal systems shall be located and constructed to avoid impairment to them or contamination from them during flooding.
- (11) Any alteration, repair, reconstruction or improvement to a structure which is not compliant with the provisions of this ordinance, shall be undertaken only if the non-conformity is not furthered, extended or replaced.
- (12) Proposed new construction and substantial improvements that are partially located in an area of special flood hazard shall have the entire structure meet the standards for new construction.
- (13) Proposed new construction and substantial improvements that are located in multiple flood hazard risk zones or in a flood hazard risk zone with multiple base flood elevations shall have the entire structure meet the standards for the most hazardous flood hazard risk zone and the highest base flood elevation.

## **SECTION B.           SPECIFIC STANDARDS**

In ALL Areas of Special Flood Hazard designated as A1-30, AE, AH, A (with engineered or estimated base flood elevation), the following provisions are required:

### **(1) Residential and Non-residential Structures**

- (a) Where base flood elevation data is available, new construction and substantial improvement of any structure or manufactured home shall have the lowest floor, including basement, elevated no lower than two (2) foot above the base flood elevation.
- (b) All heating and air conditioning equipment and components, all electrical, ventilation, plumbing, and other service facilities shall be designed and/or located a minimum of two (2) feet above the BFE to prevent water from entering or accumulating within the components during conditions of flooding.
- (c) Foundations shall be in accordance with the standards of Article 4, Sections B(3) and B(4). Should solid foundation perimeter walls be used to elevate a structure, openings sufficient to facilitate the unimpeded movements of flood waters shall be provided.

### **(2) Non-Residential Structures**

- (a) New construction and substantial improvement of any non-residential structure located in A1-30, AE, or AH zones, may be floodproofed in lieu of elevation.
  - (i) The structure, together with attendant utility and sanitary facilities, must be designed to be water tight to two (2) foot above the base flood elevation, with walls substantially impermeable to the passage of water, and structural components having

the capability of resisting hydrostatic and hydrodynamic loads and the effect of buoyancy.

- (ii) A registered professional engineer or architect shall certify that the design and methods of construction are in accordance with accepted standards of practice for meeting the provisions above, and shall provide such certification to the official as set forth above and in Article 3, Section C(6).
- (b) Dry floodproofing is allowed only in areas where flood velocities are less than or equal to five feet per second. A registered professional engineer or architect shall certify that the standards of this subsection are satisfied. A Flood Emergency Operation Plan and an Inspection and Maintenance Plan must be provided by the design professional for the building. Such certification shall be provided to the Floodplain Administrator.

(3) Foundations for Elevated Buildings

- (a) A registered professional engineer or architect shall certify that the design and methods of construction are in accordance with accepted standards of practice for provisions of Article 4, Section A, and shall provide such plans and certification to the Floodplain Administrator as set forth in Article 3, Section B for any of the following:
  - (i) Foundations greater than 36” above the lowest adjacent grade.
  - (ii) All foundations located in the designated floodway.

(4) Enclosures for Elevated Buildings

All new construction and substantial improvements of existing structures that include **ANY fully enclosed area** below the base flood elevation, located below the lowest floor formed by the foundation and other exterior walls shall be designed to be an unfinished or flood resistant enclosure. The enclosure shall be designed to equalize hydrostatic flood forces on exterior walls by allowing for the automatic entry and exit of flood waters.

- (a) Designs for complying with this requirement must either be certified by a professional engineer or architect or meet the following minimum criteria:
  - (i) Provide a minimum of two openings, located on opposite sides of each enclosed area having a total net area of not less than one square inch for every square foot of enclosed area subject to flooding (if a structure has more than one enclosed area below the base flood elevation, each shall have openings on exterior walls);
  - (ii) The bottom of all openings shall be no higher than one foot above grade; and
  - (iii) Openings may be equipped with screens, louvers, valves and other coverings and devices provided they permit the automatic flow of floodwater in both directions.
  - (iv) Foundations shall be no greater than 36” in height above the lowest adjacent grade.
- (b) So as not to violate the "Lowest Floor" criteria of this ordinance, the unfinished or flood resistant enclosure shall only be used for parking of vehicles, limited storage of maintenance equipment used in connection with the premises, or entry to the elevated area.
- (c) The interior portion of such enclosed area shall not be partitioned or finished into separate rooms. All interior walls, ceilings and floors below the base flood elevation shall be unfinished and/or constructed of flood resistant materials.
- (d) Mechanical, electrical or plumbing devices shall not be installed below the freeboard elevation (Base Flood Elevation plus two (2) feet). The interior portion of such enclosed area(s) shall be void of utilities except for essential lighting and power as required.
- (e) Property owners shall be required to execute a flood openings/venting affidavit, on forms provided by the Community. Property owners shall agree, certify, and declare to the following conditions as a condition for granting a permit:

- (i) That the enclosed area(s) shall remain fully compliant with all parts of the section Enclosures for Elevated Buildings of this Ordinance unless otherwise modified to be fully compliant with the applicable sections of the Flood Damage Prevention Ordinance in effect at the time of conversion.
- (ii) A duly appointed representative of the Community is authorized to enter the property for the purpose of inspecting the exterior and interior of the enclosed area to verify compliance with the Agreement and Permit.
- (iii) The community may take any appropriate legal action to correct any violation pertaining to the Agreement and the subject Permit.

(5) Standards for Manufactured Homes and Recreational Vehicles

- (a) Where base flood elevation data are available, all manufactured homes placed and substantially improved on:
  - (i) individual lots or parcels,
  - (ii) in new or substantially improved manufactured home parks or subdivisions,
  - (iii) in expansions to existing manufactured home parks or subdivisions, or
  - (iv) on a site in an existing manufactured home park or subdivision where a manufactured home has incurred "substantial damage",
 must have the lowest floor including basement elevated no lower than two (2) foot above the base flood elevation including all heating and air conditioning equipment and components, all electrical, ventilation, plumbing, and other service facilities.
- (b) Manufactured homes placed and substantially improved in an existing manufactured home park or subdivision may be elevated so that either:
  - (i) the lowest floor of the manufactured home is elevated no lower than two (2) foot above the level of the base flood elevation including all heating and air conditioning equipment and components, all electrical, ventilation, plumbing, and other service facilities.
  - (ii) where no Base Flood Elevation exists, the manufactured home chassis and supporting equipment is supported by reinforced piers or other foundation elements of at least equivalent strength and is elevated to a maximum of 60 inches (five feet) above grade including all heating and air conditioning equipment and components, all electrical, ventilation, plumbing, and other service facilities.
- (c) All Manufactured homes must be securely anchored to an adequately anchored foundation system to resist flotation, collapse and lateral movement.
- (d) Foundations shall be in accordance with the standards of Article 4, Sections B(3) & B(4).
- (e) All recreational vehicles placed on sites must either:
  - (i) be on the site for fewer than 180 consecutive days, fully licensed and ready for highway use if it is licensed, on its wheels or jacking system, attached to the site only by quick disconnect type utilities and security devices, and has no permanently attached structures or additions; or
  - (ii) the recreational vehicle must meet all the requirements for "New Construction", as set forth in this ordinance, including the anchoring and elevation requirements.

- (6) Require, until a regulatory floodway is designated, that no new construction, substantial improvements, or other development (including fill) shall be permitted within Zones A1-30 and AE on the Community's FIRM, unless it is demonstrated that the cumulative effect of the proposed development, when combined with all other existing and anticipated development, will not increase the water surface elevation of the base flood more than **one foot** at any point within the community.

- (7) Accessory Structures (also referred to as appurtenant structures) – This provision generally applies to new and substantially improved accessory structures. When an accessory structure complies with all other provisions of this ordinance (including floodway encroachment), represents a minimal investment of less than \$5000, and meets the requirements outlined below, these structures may be wet-floodproofed and do not have to be elevated or dry floodproofed.

Accessory structures include, but are not limited to, residential structures such as detached garages, storage sheds for garden tools or woodworking, gazebos, picnic pavilions, boathouses, small pole barns, agricultural structures, and similar buildings. The following provisions apply to accessory structures built below the base flood elevation:

- (a) A permit shall be required prior to construction or installation.
- (b) Must be low value (less than \$5000) and not be used for human habitation.
- (c) Use must be restricted to parking of personal vehicles or limited storage (low-cost items that cannot be conveniently stored in the principal structure).
- (d) Must be designed with an unfinished interior and constructed with flood damage-resistant materials below the BFE.
- (e) Must be adequately anchored to prevent flotation, collapse, or lateral movement.
- (f) Must have adequate flood openings as described in Article 4, Section B (4) and be designed to otherwise have low flood damage potential.
- (g) Shall be constructed and placed on the building site so as to offer the minimum resistance to the flow of floodwaters.
- (h) Any mechanical and other utility equipment in the structure must meet the elevation requirements of Article 4, Section B(1)(b) and Section D(5) or must be floodproofed.
- (i) Under special exceptions, the Floodplain Administrator may permit construction of wet-floodproofed accessory structures of value \$5000 or greater, and:
  - (i) Should not be issued to entire subdivisions, especially detached garages.
  - (ii) Should only be reviewed and issued on an individual or case-by-case basis and be based on the unique characteristics of the site.
  - (iii) Must be the minimum necessary and must be consistent with the need to minimize damage and must be consistent with requirements of Article 4, Section B(7) herein.

## **SECTION C. FLOODWAYS**

Located within Areas of Special Flood Hazard established in Article 2, Section B, are areas designated as floodway. A floodway may be an extremely hazardous area due to velocity floodwaters, debris or erosion potential. In addition, the area must remain free of encroachment in order to allow for the discharge of the base flood without increased flood heights. Therefore, the following provisions shall apply:

- (1) The community shall select and adopt a regulatory floodway based on the principle that the area chosen for the regulatory floodway must be designed to carry the waters of the base flood, without increasing the water surface elevation of that flood more than one foot at any point;
- (2) Encroachments are prohibited, including fill, new construction, substantial improvements or other development within the adopted regulatory floodway. Development may be permitted however, provided it is demonstrated through hydrologic and hydraulic analyses performed in accordance with standard engineering practice that the encroachment **shall not result in any increase** in flood levels or floodway widths during a base flood discharge. A “**No-Rise / No**

**Impact”** certification shall be required from a registered professional engineer and supporting technical data and certification thereof must be provided;

- (3) A community may permit encroachments within the adopted regulatory floodway that would result in an increase in base flood elevations, provided that the community first applies for a conditional letter of map revision (CLOMR) and floodway revision, fulfills the requirements for such revisions as established under the provisions of § 65.12, and receives the approval of FEMA; the permit holder (property owner, developer, etc.) shall pay all cost.
- (4) **ONLY** if Article 4, Section C, provisions (1) through (3) are satisfied, then any new construction or substantial improvement shall comply with all other applicable flood hazard reduction provisions of Article 4.

**SECTION D. BUILDING STANDARDS FOR STREAMS WITHOUT ESTABLISHED BASE FLOOD ELEVATIONS (APPROXIMATE A-ZONES)**

Located within the Areas of Special Flood Hazard established in Article 2, Section B, where streams exist but no base flood data have been provided (Approximate A-Zones), the following provisions apply:

- (1) Base flood elevation data shall be provided for subdivision proposals and all other proposed development, including manufactured home parks and subdivisions, greater than fifty (50) lots or five (5) acres, whichever is the lesser.
- (2) When base flood elevation data or floodway data have not been provided in accordance with Article 2, Section B then the Floodplain Administrator shall obtain, review, and reasonably utilize any scientific or historic Base Flood Elevation and floodway data available from a Federal, State, or other source, in order to administer the provisions of Article 4. **ONLY** if data is not available from these sources, then Article 4, Section D, provisions (5) and (6) shall apply.
- (3) No encroachments, including structures or fill material, shall be located within an area equal to the width of the stream or twenty-five feet, whichever is greater, measured from the top of the stream bank, unless certification by a registered professional engineer is provided demonstrating that such encroachment shall not result in any increase in flood levels during the occurrence of the base flood discharge.
- (4) All development in Zone A must meet the requirements of Article 4, Section A and Section B(1) through B(5).
- (5) In special flood hazard areas without base flood elevation data, new construction and substantial improvements of existing structures shall have the lowest floor (for the lowest enclosed area; including basement) elevated no less than five (5) feet above the highest adjacent grade including all heating and air conditioning equipment and components, all electrical, ventilation, plumbing, and other service facilities.
- (6) In the absence of a base flood elevation, a manufactured home must also meet the elevation requirements of Article 4, Section B(5)(b)(ii) in that the structure must be elevated to a maximum of 60 inches (5 feet).
- (7) Openings sufficient to facilitate automatic equalization of flood water hydrostatic forces on exterior walls shall be provided in accordance with standards of Article 4, Section B(4)(a). The

Floodplain Administrator shall certify the lowest floor elevation level, utilizing information from Article 3, Section B, and the record shall become a permanent part of the permit file.

**SECTION E                    STANDARDS FOR AREAS OF SHALLOW FLOODING (AO ZONES)**

Areas of Special Flood Hazard established in Article 2, Section B may include designated "AO" shallow flooding areas. These areas have base flood depths of one to three feet (1'-3') above ground, with no clearly defined channel. The following provisions apply:

- (1) All new construction and substantial improvements of residential and nonresidential structures shall have the lowest floor, including basement, all heating and air conditioning equipment and components, all electrical, ventilation, plumbing, and other service facilities, elevated above the highest adjacent grade at least as high as the depth number specified on the Flood Insurance Rate Map (FIRM) plus two (2) foot of freeboard. If no depth number is specified, the lowest floor, including basement, all heating and air conditioning equipment and components, all electrical, ventilation, plumbing, and other service facilities shall be elevated at least five (5) feet above the highest adjacent grade. Openings sufficient to facilitate the unimpeded movements of flood waters shall be provided in accordance with standards of Article 4, Section B(4)(a). The Floodplain Administrator shall certify the lowest floor elevation level and the record shall become a permanent part of the permit file, utilizing information from Article 3, Section B.
- (2) New construction and the substantial improvement of a non-residential structure may be flood-proofed in lieu of elevation. The structure, together with attendant utility and sanitary facilities, must be designed to be water tight to the specified flood level in Article 4, Section E(1) or five (5) feet (if no depth number is specified), above highest adjacent grade, with walls substantially impermeable to the passage of water, and structural components having the capability of resisting hydrostatic and hydrodynamic loads and the effect of buoyancy. A registered professional engineer or architect shall certify that the design and methods of construction are in accordance with accepted standards of practice for meeting the provisions above, and shall provide such certifications to the official as set forth above and as required in Article 3, Section B.
- (3) Drainage paths shall be provided to guide floodwater around and away from any proposed structure.

**SECTION F                    STANDARDS FOR SUBDIVISIONS**

- (1) All subdivision proposals shall be consistent with the need to minimize flood damage.
- (2) All subdivision proposals shall have public utilities and facilities such as sewer, gas, electrical and water systems located and constructed to minimize flood damage.
- (3) All subdivision proposals shall have adequate drainage provided to reduce exposure to flood hazards, and;
- (4) Base flood elevation data shall be provided for all new subdivision proposals and other proposed development (including manufactured home parks and subdivisions), which is greater than fifty lots or five acres; whichever is the lesser.
- (5) All preliminary plans for platted subdivisions shall identify the flood hazard area and the elevation of the base flood.

- (6) All final subdivision plats will provide the boundary of the special flood hazard area, the floodway boundary, and the base flood elevations.
- (7) All Subdivision proposals shall be submitted to the Morgan County Engineer for approval.

**ARTICLE 5**  
**VARIANCE PROCEDURES**

**SECTION A.           DESIGNATION OF VARIANCE AND APPEALS BOARD**

The **Morgan County Commission, Morgan County, Alabama** shall function as the **Morgan County Appeal Board** and shall hear and decide requests for appeals or variance from the requirements of this ordinance.

**SECTION B.           DUTIES OF BOARD**

The Board shall hear and decide appeals when it is alleged an error in any requirement, decision, or determination is made by the Floodplain Administrator in the enforcement or administration of this ordinance. Any person aggrieved by the decision of the **Morgan County Appeal Board** may appeal such decision to the **Morgan County Circuit Court**, as provided in §11-19-20, Code of Alabama, 1975.

**SECTION C.           VARIANCE PROCEDURES**

In reviewing requests for variance, the **Morgan County Appeal Board** shall consider all technical evaluations, relevant factors, and standards specified in other sections of this ordinance, and:

- (1) Variances may be issued for development necessary for the conduct of a functionally dependent use, provided the criteria of this Article are met, no feasible alternative exists, the development is protected by methods that minimize flood damage during the base flood, and it creates no additional threats to public safety.
- (2) Variances shall not be issued within any designated floodway if ANY increase in flood levels or floodway widths during the base flood discharge would result.
- (3) Variances may be issued based on an exceptional hardship. The evaluation must be based on the characteristics unique to that property and not be shared by adjacent parcels. The characteristics must pertain to the land itself, not to the structure, its inhabitants, or its owners. Mere economic or financial hardship alone is NOT exceptional. Inconvenience, aesthetic considerations, physical handicaps, personal preferences, or the disapproval of one’s neighbors likewise cannot, as a rule, qualify as an exceptional hardship.
- (4) Variances should never be granted for multiple lots, phases of subdivisions, or entire subdivisions.
- (5) The danger of life and property due to flooding or erosion damage including materials that may be swept onto other lands to the injury of others.
- (6) The susceptibility of the proposed facility and its contents to flood damage and the effect of such damage on the individual owner and the community.



- (7) The safety of access to the property during flood conditions for daily traffic and emergency vehicles.
- (8) The importance of the services provided by the proposed facility to the community.
- (9) The necessity of the facility to be at a waterfront location, where applicable.
- (10) The compatibility of the proposed use with existing and anticipated development based on the community's comprehensive plan for that area.
- (11) The expected heights, velocity, duration, rate of rise, and sediment transport of the floodwaters and the effects of wave action, if applicable, expected at the site.
- (12) The costs associated with providing governmental services to the development during and after flood conditions, including maintenance and repair of public utilities and facilities such as sewer, gas, electrical, and water systems, and community infrastructure such as streets, bridges, and culverts.

Upon consideration of factors listed above, and the purpose of this ordinance, the **Morgan County Appeal Board** may attach such conditions to the granting of variances as it deems necessary to further the purposes of this ordinance.

**SECTION D. VARIANCES FOR HISTORIC STRUCTURES**

Variances may be issued for the repair or rehabilitation of Historic Structures upon a determination that the proposed repair or rehabilitation will not preclude the structure's continued designation as a Historic Structure and the variance is the minimum to preserve the historic character and design of the structure.

**SECTION E. CONDITIONS FOR VARIANCES**

The provisions of this Ordinance are minimum standards for flood loss reduction, therefore any deviation from the standards must be weighed carefully. Variances shall only be issued upon a determination that the variance is the minimum necessary, considering the flood hazard, to afford relief.

- (1) In the instance of a Historic Structure, a determination is required that the variance is the minimum necessary so as not to destroy the historic character and design of the building.
- (2) A variance shall be issued ONLY when there is:
  - (a) A finding of good and sufficient cause;
  - (b) A determination that failure to grant the variance would result in exceptional hardship; and
  - (c) A determination that the granting of a variance will not result in increased flood heights, additional threats to public safety, extraordinary public expense, create nuisance, cause fraud on or victimization of the public, or conflict with existing local laws or ordinances.
- (3) Variances shall not be issued "after the fact."

**SECTION F. VARIANCE NOTIFICATION AND RECORDS**

Any applicant to whom a variance is granted shall be given written notice over the signature of a community official that:

- (1) Specifies the difference between the base flood elevation and the elevation of the proposed lowest floor and stating that the cost of flood insurance will be commensurate with an increased risk to life and property resulting from the reduced lowest floor elevation. It could result in rate increases in the hundreds and possibly thousands of dollars annually depending on structure and site-specific conditions.
- (2) The Floodplain Administrator shall maintain a record of all variance actions and appeal actions, including justification for their issuance. Report any variances to the Federal Emergency Management Agency Region 4 and the Alabama Department of Economic and Community Affairs/Office of Water Resources upon request.
- (3) A copy of the notice shall be recorded by the Floodplain Administrator in the Office of the **Morgan County Engineer** and shall be recorded in a manner so that it appears in the chain of title of the affected parcel of land.

## ARTICLE 6

### DEFINITIONS

Unless specifically defined below, words or phrases used in this ordinance shall be interpreted so as to give them the meaning they have in common usage and to give this ordinance its most reasonable application.

**A Zone** means the Area of Special Flood Hazard without base flood elevations determined.

**Accessory Structure (also referred to as appurtenant structures)** means a structure which is located on the same parcel of property as a principal structure to be insured and the use of which is incidental to the use of the principal structure. They should constitute a minimal initial investment, may not be used for human habitation, and be designed to have minimal flood damage potential. These structures are used solely for parking (two-car detached garages or smaller), limited storage (small, low cost storage sheds), or agricultural structures. They are included under the general definition of structure and are consequently subject to all floodplain management regulations pertaining to structures.

**Addition (to an existing building)** means any improvement that increases the square footage of a structure. These include lateral additions added to the front, side, or rear of a structure, vertical additions added on top of a structure, and enclosures added underneath a structure. NFIP regulations for new construction apply to any addition that is considered a perimeter expansion or enclosure beneath a structure. If it is considered to be a substantial improvement (more than 50% of market value) to a structure, the existing structure will also need to be treated as new construction.

Depending on the flood zone and details of the project, the existing building may not have to be elevated. The determining factors are the common wall and what improvements are made to the existing structure. If the common wall is demolished as part of the project, then the entire structure must be elevated. If only a doorway is knocked through it and only minimal finishing is done, then only the addition has to be elevated.

**AE Zone** means the Area of Special Flood Hazard with base flood elevations determined.

**AH Zone** means an area of one percent chance of shallow flooding where depths are between one to three feet (usually shallow ponding), with base flood elevations shown.

**AO Zone** means an area of one percent chance of shallow flooding where depths are between one to three feet (usually sheet flow on sloping terrain), with depth numbers shown.

**Appeal** means a request for a review of the Floodplain Administrator’s interpretation of any provision of this ordinance.

**AR/AE, AR/AH, AR/AO, and AR/A Zones** means a flood zone that results from the decertification of a previously accredited flood protection system or levee that is in the process of being restored to provide a one percent chance or greater level of flood protection. After restoration is complete, these areas will still experience residual flooding from other flooding sources.

**A99 Zone** means that part of the special flood hazard area inundated by the one percent annual chance flood to be protected from the one percent chance flood by a Federal flood protection system or levee under construction, no base flood elevations are determined.

**Area of shallow flooding** means a designated AO or AH Zone on a community's Flood Insurance Rate Map (FIRM) with base flood depths from one to three feet, and/or where a clearly defined channel does not exist, where the path of flooding is unpredictable and indeterminate, and where velocity flow may be evident.

**Area of special flood hazard** means the land in the floodplain within a community subject to a one percent or greater chance of flooding in any given year. In the absence of official designation by the Federal Emergency Management Agency, Areas of Special Flood Hazard shall be those designated by the local community and referenced in Article 2, Section B.

**Base flood** means the flood having a one percent chance of being equaled or exceeded in any given year (also referred to as the “one percent chance flood”).

**Base flood elevation** means the computed elevation to which floodwater is anticipated to rise during the base flood. It is also the elevation of surface water resulting from a flood that has a 1% chance of equaling or exceeding that level in any given year. Base Flood Elevations are shown in the FIS and on the Flood Insurance Rate Map (FIRM) for zones AE, AH, A1–A30, AR, AR/A, AR/AE, AR/A1– A30, AR/AH, AR/AO, V1–V30 and VE.

**Basement** means any portion of a building having its floor sub grade (below ground level) on all sides.

**Building** (also see Structure) means

- (1) A structure with 2 or more outside rigid walls and a fully secured roof, that is affixed to a permanent site; or
- (2) a manufactured home (a “manufactured home,” also known as a mobile home, is a structure built on a permanent chassis, transported to its site in 1 or more sections, and affixed to a permanent foundation); or

- (3) a travel trailer without wheels, built on a chassis and affixed to a permanent foundation, that is regulated under the community's floodplain management and building ordinances or laws..

**Community** means a political entity and/or its authorized agents or representatives that have the authority to adopt and enforce floodplain ordinances for the area under its jurisdiction.

**Community Rating System (CRS)** means a program developed by the Federal Insurance Administration to provide incentives for those communities in the Regular Program that have gone beyond the minimum floodplain management requirements to develop extra measures to provide protection from flooding.

**D Zone** means an area in which the flood hazard is undetermined.

**Dam** means any artificial barrier, including appurtenant works, constructed to impound or divert water, waste water, liquid borne materials, or solids that may flow if saturated. All structures necessary to maintain the water level in an impoundment or to divert a stream from its course will be considered a dam.

**Development** means any man-made change to improved or unimproved real estate, including, but not limited to, buildings or other structures, mining, dredging, filling, grading, paving, excavation, drilling operations, or storage of equipment or materials.

**Dry Floodproofing** means any combination of structural and nonstructural additions, changes, or adjustments to structures, which reduce or eliminate flood damages to real estate or improved real estate property, water, and sanitary facilities, structures, and their contents. Structures shall be floodproofed with a minimum of 24 inches above the base flood elevation (more is recommended). Dry floodproofing of a pre-FIRM residential structure that has not been substantially damaged or improved is allowed. Dry floodproofing of a post- FIRM residential building is not allowed. Non-residential structures may be dry floodproofed in all flood zones with the exception of the Coastal High Hazard Area or the Coastal AE Zone.

**Elevated building** means a non-basement building which has its lowest elevated floor raised above ground level by foundation walls, pilings, posts, columns, piers, or shear walls.

**Elevation Certificate** means a FEMA form used as a certified statement that verifies a building's elevation information.

**Encroachment** means the advance or infringement of uses, plant growth, fill, excavation, buildings, structures or development into a floodplain, which may impede or alter the flow capacity of a floodplain.

**Existing Construction** means any structure for which the "start of construction" commenced before February 25, 1991 or before January 1, 1975, for FIRMs effective before that date. Existing construction may also be referred to as existing structures.

**Existing manufactured home park or subdivision** means a manufactured home park or subdivision for which the construction of facilities for servicing the lots on which the manufactured

homes are to be affixed (including at a minimum the installation of utilities, the construction of streets, and final site grading or the pouring of concrete pads) is completed before February 25, 1991.

**Expansion to an existing manufactured home park or subdivision** means the preparation of additional sites by the construction of facilities for servicing the lots on which the manufactured homes are to be affixed, including the installation of utilities, the construction of streets, and either final site grading or the pouring of concrete pads.

**FEMA** means Federal Emergency Management Agency

**FEMA Technical Bulletins** means FEMA published guidance and technical bulletins that outline how to administer floodplain management regulations in specific development situations. New bulletins as well as updates of existing bulletins are issued periodically as needed. The documents don't add regulations, but clarify the requirements established in this ordinance. These technical bulletins do not replace any higher standards that may be in place. Typical publications include, but are not limited to the following:

- (a) "Technical Bulletin 1, Openings in Foundation Walls and Walls of Enclosures (2008)"
- (b) "Technical Bulletin 2, Flood Damage-Resistant Materials Requirements (2008)"
- (c) "Technical Bulletin 3, Non-Residential Floodproofing - Requirements and Certification (1993)"
- (d) "Technical Bulletin 4, Elevator Installation (2010)"
- (e) "Technical Bulletin 6, Below-Grade Parking Requirements (1993)"
- (f) "Technical Bulletin 7, Wet Floodproofing Requirements (1993)"
- (g) "Technical Bulletin 10, Ensuring that Structures Built on Fill In or Near Special Flood Hazard Areas are Reasonably Safe From Flooding (2001)"
- (h) "Technical Bulletin 11, Crawlspace Construction for Buildings Located in Special Flood Hazard Areas (2001)"
- (i) "FEMA P-85, Second Edition, Protecting Manufactured Homes from Floods and Other Hazards, A Multi-Hazard Foundation and Installation Guide, (November 2009)"

**Flood or flooding** means a general and temporary condition of partial or complete inundation of normally dry land areas from:

- (a) The overflow of inland or tidal waters; or
- (b) The unusual and rapid accumulation or runoff of surface waters from any source.
- (c) Mudslides which are proximately caused by flooding as described in part "b." of this definition and are akin to a river of liquid and flowing mud on the surfaces of normally dry land areas, as when earth is carried by a current of water and deposited along the path of the current.
- (d) The collapse or subsidence of land along the shore of a lake or other body of water as a result of erosion or undermining caused by waves or currents of water exceeding anticipated cyclical levels or suddenly caused by an unusually highwater level in a natural body of water, accompanied by a severe storm, or by an unanticipated force of nature, such as flash flood or an abnormal tidal surge, or by some similarly unusual and unforeseeable event which results in flooding as defined in part "a." of this definition.

**Flood Hazard Boundary Map (FHBM)** means an official map of a community, issued by the Federal Insurance Administration, where the boundaries of areas of special flood hazard have been designated as Zone A.

**Flood Insurance Rate Map (FIRM)** means an official map of a community, on which the Federal Emergency Management Agency has delineated the areas of special flood hazard and/or risk premium zones applicable to the community.

**Flood Insurance Study/ Flood Elevation Study** means an examination, evaluation and determination of flood hazards and, if appropriate, corresponding water surface elevations, or an examination, evaluation and determination of mudslide and/or flood-related erosion hazards.

**Floodplain** means any land area susceptible to being inundated by water from any source.

**Floodplain management** means the operation of an overall program of corrective and preventive measures for reducing flood damage and preserving and enhancing, where possible, natural resources in the floodplain, including but not limited to emergency preparedness plans, flood control works, floodplain management regulations, and open space plans.

**Floodplain management regulations** means this ordinance and other zoning ordinances, subdivision regulations, building codes, health regulations, special purpose ordinances, and other applications of police power which control development in flood-prone areas. This term describes federal, state, or local regulations in any combination thereof, which provide standards for preventing and reducing flood loss and damage.

**Floodproofing** means any combination of structural and nonstructural additions, changes or adjustments to structures, which reduce or eliminate risk of flood damage to real estate or improved real property, water and sanitation facilities or structures with their contents.

**Floodway (Regulatory Floodway)** means the channel of a river or other watercourse and the adjacent land areas that must be reserved in order to discharge the base flood without cumulatively increasing the water surface elevation more than a designated height.

**Floodway fringe** means that area of the special flood hazard area on either side of the regulatory floodway.

**Flood Protection Elevation** means the base flood elevation plus the community freeboard. In areas where no base flood elevations exist from any authoritative source, the flood protection elevation can be historical flood elevations or base flood elevations determined and/or approved by the floodplain administrator plus freeboard.

**Freeboard** means an additional amount of height above the Base Flood Elevation used as a factor of safety in determining the level at which a structure's lowest floor, heating and air conditioning equipment and components, all electrical, ventilation, plumbing, and other service facilities must be elevated or floodproofed to be in accordance with this ordinance. For the purpose of this Ordinance, the freeboard is two (2) feet above the BFE.

**Functionally dependent facility** means a facility which cannot be used for its intended purpose unless it is located or carried out in close proximity to water. The term includes only docking facilities, port facility that are necessary for the loading and unloading of cargo or passengers, and shipbuilding, and ship repair facilities. The term does not include long-term storage or related manufacturing facilities.

**Hardship** (as related to variances of this ordinance) means the exceptional difficulty that would result from a failure to grant the requested variance. The **Morgan County Commission** requires that the variance is exceptional, unusual, and peculiar to the property involved. Mere economic or financial hardship alone is NOT exceptional. Inconvenience, aesthetic considerations, physical handicaps, personal preferences, or the disapproval of one's neighbors likewise cannot, as a rule, qualify as an exceptional hardship. All of these problems can be resolved through other means without granting a variance, even if the alternative is more expensive, or requires the property owner to build elsewhere or put the parcel to a different use than originally intended.

**Highest adjacent grade** means the highest natural elevation of the ground surface, prior to construction, next to the proposed walls of a structure.

**Historic Structure** means any structure that is;

- (a) Listed individually in the National Register of Historic Places (a listing maintained by the U.S. Department of Interior) or preliminarily determined by the Secretary of the Interior as meeting the requirements for individual listing on the National Register:
- (b) Certified or preliminarily determined by the Secretary of the Interior as contributing to the historical significance of a registered historic district or a district preliminarily determined by the Secretary to qualify as a registered historic district:
- (c) Individually listed on a state inventory of historic places and determined as eligible by states with historic preservation programs which have been approved by the Secretary of the Interior; or
- (d) Individually listed on a local inventory of historic places and determined as eligible by communities with historic preservation programs that have been certified either:
  - (i) By an approved state program as determined by the Secretary of the Interior, or
  - (ii) Directly by the Secretary of the Interior in states without approved programs.

**Letter of Map Change (LOMC)** is an official FEMA determination, by letter, to amend or revise effective Flood Insurance Rate Maps, Flood Boundary and Floodway Maps, and Flood Insurance Studies. LOMC's are broken down into the following categories:

**Letter of Map Amendment (LOMA)**

An amendment based on technical data showing that a property was incorrectly included in a designated SFHA, was not elevated by fill (only by a natural grade elevation), and will not be inundated by the one percent chance flood. A LOMA amends the current effective FIRM and establishes that a specific property is not located in a SFHA.

**Letter of Map Revision (LOMR)**

A revision based on technical data that, usually due to manmade changes, shows changes to flood zones, flood elevations, floodplain and floodway delineations, and planimetric features. One common type of LOMR, a LOMR-F, is a determination concerning whether a structure or parcel has been elevated by fill above the BFE and is, therefore, excluded from the SFHA.

**Conditional Letter of Map Revision (CLOMR)**

A formal review and comment by FEMA as to whether a proposed project complies with the minimum NFIP floodplain management criteria. A CLOMR does not revise effective Flood Insurance Rate Maps, Flood Boundary and Floodway Maps, or Flood Insurance Studies.

**Levee** means a man-made structure, usually an earthen embankment, designed and constructed in accordance with sound engineering practices to contain, control, or divert the flow of water so as to provide protection from temporary flooding.

**Levee System** means a flood protection system which consists of a levee, or levees, and associated structures, such as closure and drainage devices, which are constructed and operated in accordance with sound engineering practices.

**Lowest adjacent grade** means the point of the ground level immediately next to a building. This may be the sidewalk, patio, deck support, or basement entryway immediately next to the structure after the completion of construction. It does not include earth that is placed for aesthetic or landscape reasons around a foundation wall. It does include natural ground or properly compacted fill that comprises a component of a building's foundation system.

**Lowest floor** means the lowest floor of the lowest enclosed area (including basement). An unfinished or flood resistant enclosure, used solely for parking of vehicles, building access, or storage, in an area other than a basement, is not considered a building's lowest floor, provided that such enclosure is not built so as to render the structure in violation of other provisions of this ordinance.

**Manufactured home** means a building, transportable in one or more section, built on a permanent chassis and designed to be used with or without a permanent foundation when connected to the required utilities. The term also includes park trailers, travel trailers, and similar transportable structures placed on a site for 180 consecutive days or longer and intended to be improved property.

**Manufactured home park or subdivision** means a parcel (or contiguous parcels) of land divided into two or more manufactured home lots for rent or sale.

**Market value** means the property value (as agreed between a willing buyer and seller), excluding the value of land as established by what the local real estate market will bear. Market value can be established by independent certified appraisal; replacement cost depreciated by age of building (Actual Cash Value); or adjusted assessed values.

**Mean Sea Level** means the average height of the sea for all stages of the tide. It is used as a reference for the base flood elevations shown on a community's Flood Insurance Rate Map (FIRM). For purposes of this ordinance, the term is synonymous with National Geodetic Vertical Datum (NGVD) of 1929, North American Vertical Datum (NAVD) of 1988, or other datum.

**National Flood Insurance Program (NFIP)** means the federal program that makes flood insurance available to owners of property in participating communities nationwide through the cooperative efforts of the Federal Government and the private insurance industry.



**National Geodetic Vertical Datum (NGVD)** means as corrected in 1929 is a vertical control used as a reference for establishing varying elevations within the floodplain.

**New construction** means ANY structure (see definition) for which the "start of construction" commenced after February 25, 1991 and includes any subsequent improvements (including additions) to such structures.

**New manufactured home park or subdivision** means a manufactured home park or subdivision for which the construction of facilities for servicing the lots on which the manufactured homes are to be affixed (including at a minimum, the installation of utilities, the construction of streets, and either final site grading or the pouring of concrete pads) is completed on or after February 25, 1991.

**No-Rise / No Impact Certification** means a FEMA form used to certify, through hydrologic and hydraulic analyses performed in accordance with standard engineering practice, that the proposed encroachment will not result in any increase in flood levels or floodway widths within the community during the occurrence of the base flood discharge. An engineering analysis must be conducted before a permit can be issued. This "No-rise / No Impact" Certification must be supported by technical data and signed by a registered professional engineer. The supporting technical data should be based on the standard step-backwater computer model used to develop the 1% annual chance floodway shown on the Flood Insurance Rate Map (FIRM) and Flood Insurance Study (FIS).

**Non-Residential** means, but is not limited to; small business concerns, churches, schools, farm buildings (including grain bins and silos), pool houses, clubhouses, recreational buildings, mercantile structures, agricultural and industrial structures, warehouses, and hotels and motels with normal room rentals for less than 6 months duration.

**North American Vertical Datum (NAVD) of 1988** means a vertical control, corrected in 1988, used as a reference for establishing varying elevations within the floodplain.

**Obstruction** means, but is not limited to, any dam, wall, wharf, embankment, levee, dike, pile, abutment, protection, excavation, channel construction, bridge, culvert, building, wire, fence, rock, gravel, refuse, fill, structure, vegetation or other material in, along, across or projecting into any watercourse which may alter, impede, retard or change the direction and/or velocity of the flow of water, or due to its location, its propensity to snare or collect debris carried by the flow of water, or its likelihood of being carried downstream.

**One Percent Flood** (aka 100-Year Flood or 1% annual chance flood) is the flood that has a one percent chance of being equaled or exceeded in any given year. Any flood zone that begins with the letter A or V is subject to inundation by the one percent chance flood. Over the life of a 30-year loan, there is a 26-percent chance of experiencing such a flood within the SFHA.

**Participating Community** is any community that voluntarily elects to participate in the NFIP by adopting and enforcing floodplain management regulations that are consistent with the standards of the NFIP.

**Post-FIRM Construction** means new construction and substantial improvements for which start of construction occurred after December 31, 1974, or on or after the effective date of the initial FIRM of the community, whichever is later.

**Pre-FIRM Construction** means new construction and substantial improvements for which start of construction occurred on or before December 31, 1974, or before the effective date of the initial FIRM of the community, whichever is later.

**Probation** means an action taken by FEMA to formally notify participating communities of the first of the two NFIP sanctions due to their failure to correct violations and deficiencies in the administration and enforcement of the local floodplain management regulations.

**Public safety and nuisance** means anything which is injurious to the safety or health of an entire community or neighborhood, or any considerable number of persons, or unlawfully obstructs the free passage or use, in the customary manner, of any navigable lake, or river, bay, stream, canal, or basin.

**Recreational vehicle** means a vehicle which is:

- a. Licensed and titled as a recreational vehicle or park model;
- b. Built on a single chassis;
- c. 400 square feet or less when measured at the largest horizontal projection;
- d. Has no attached deck, porch, or shed;
- e. Has quick-disconnect sewage, water, and electrical connectors;
- f. Designed to be self-propelled or permanently towable by a light duty truck; and
- g. Designed primarily not for use as a permanent dwelling but as temporary living quarters for recreational, camping, travel, or seasonal use.

**Regular Program** means the second phase of the community's participation in the NFIP in which second layer coverage is available based upon risk premium rates only after FEMA has completed a flood risk study for the community.

**Regulatory floodway** see **Floodway**.

**Registered Professional Engineer/ Land surveyor / Architect** means an individual, hired by the applicant, who is registered or licensed to practice their respective design profession as defined by the statutory requirements of the professional registration laws of Alabama.

**Remedy a violation** means to bring the structure or other development into compliance with State or local floodplain management regulations, or, if this is not possible, to reduce the impacts of its noncompliance. Ways that impacts may be reduced include protecting the structure or other affected development from flood damages, implementing the enforcement provisions of the ordinance or otherwise deterring future similar violations, or reducing Federal financial exposure with regard to the structure or other development.

**Repetitive Loss** means flood-related damages sustained by a structure on two separate occasions during a 10-year period for which the cost of repairs at the time of each such flood event, on the

average, equals or exceeds 25 percent of the market value of the structure before the damages occurred.

**Repetitive Loss Property** means any insurable structure for which two or more claims of more than \$1,000 were paid by the National Flood Insurance Program (NFIP) within any rolling 10-year period, since 1978. At least two of the claims must be more than ten days apart but, within ten years of each other. A repetitive loss property may or may not be currently insured by the NFIP.

**Section 1316** means no new flood insurance policy or federal disaster assistance shall be provided for any property which the Administrator finds has been declared by a duly constituted State or local zoning authority or other authorized public body, to be in violation of State or local laws, regulations or ordinances which are intended to discourage or otherwise restrict land development or occupancy in floodprone areas. If the structure is made compliant with the applicable community's floodplain management ordinance, then the Section 1316 declaration can be rescinded by the community and flood insurance and disaster assistance eligibility restored.

**Severe Repetitive Loss Structure** means any insured property that has met at least one of the following paid flood loss criteria since 1978, regardless of ownership:

- a. Four or more separate claim payments of more than \$5,000 each (including building and contents payments); or
- b. Two or more separate claim payments (building payments only) where the total of the payments exceeds the current market value of the property.

In either case, two of the claim payments must have occurred within ten years of each other. Multiple losses at the same location within ten days of each other are counted as one loss, with the payment amounts added together.

**Special flood hazard area (SFHA)** means that portion of the floodplain subject to inundation by the base flood and/or flood-related erosion hazards as shown on a FHBM or FIRM as Zones A, AE, AH, AO, AR, AR/AE, AR/AO, AR/AH, AR/A, A99, or VE.

**Start of construction** (for other than new construction or substantial improvements under the Coastal Barrier Resources Act (Pub. L. 97-348)) means the date the development or building permit was issued (includes substantial improvement), provided the actual start of construction, repair, reconstruction, or improvement was within 180 days of the permit date. The actual start means the first placement of permanent construction of the structure (including a manufactured home) on a site, such as the pouring of slabs or footings, installation of piles, construction of columns, or any work beyond the stage of excavation, and includes the placement of a manufactured home on a foundation.

“Permanent construction”, for the purpose of defining the “Start of construction”, does not include initial land preparation, such as clearing, grading and filling; nor does it include the installation of streets and/or walkways; nor does it include excavation for a basement, footings, piers or foundations or the erection of temporary forms; nor does it include the installation on the property of buildings appurtenant to the permitted structure, such as garages or sheds not occupied as dwelling units or part of the main structure. (*NOTE: accessory structures are NOT exempt from any ordinance requirements*). For a substantial improvement, the actual start of construction means the

first alteration of any wall, ceiling, floor, or other structural part of a building, whether or not that alteration affects the external dimensions of the building.

**Structure** means a walled and roofed building, including a liquid or gas storage tank, that is principally above ground, as well as a manufactured home.

**Substantial damage** means damage of any origin sustained by a structure whereby the cost of restoring the structure to it before damaged condition would equal or exceed 50 percent of the market value of the structure before the damage occurred. Substantial damage also means flood related damages sustained by a structure on two separate occasions during a 10-year period for which the cost of repairs at the time of each such flood event, on the average, equals or exceeds 25 percent of the market value of the structure before the damages occurred.

**Substantial improvement** means any reconstruction, rehabilitation, addition, or other improvement of a structure, the cost of which equals or exceeds 50 percent of the market value of the structure before the “start of construction” of the improvement. This term includes structures which have incurred “repetitive loss” or “substantial damage”, regardless of the actual repair work performed. The market value of the building should be (1) the appraised value of the structure prior to the start of the initial repair or improvement, or (2) in the case of damage, the value of the structure prior to the damage occurring.

For the purposes of this definition, "substantial improvement" is considered to occur when the first alteration of any wall, ceiling, floor, or other structural part of the building commences, whether or not that alteration affects the external dimensions of the building. The term does not, however, include either:

- (a) Any project for improvement of a structure to correct existing violations of state or local health, sanitary, or safety code specifications which have been identified by the local code enforcement official and which are the minimum necessary to assure safe living conditions or;
- (b) Any alteration of a “historic structure”, provided that the alteration will not preclude the structure’s continued designation as a “historic structure”.

**Substantially improved existing manufactured home parks or subdivisions** is where the repair, reconstruction, rehabilitation or improvement of the streets, utilities and pads equals or exceeds 50 percent of the value of the streets, utilities and pads before the repair, reconstruction or improvement commenced.

**Suspension** means the removal, with or without probation, of a participating community from the NFIP because the community failed to adopt and enforce the compliant floodplain management regulations required for participation in the NFIP.

**Variance** means a grant of relief from the requirements of this ordinance which permits construction in a manner otherwise prohibited by this ordinance.

**Violation** means the failure of a structure or other development to be fully compliant with the community's flood plain management regulations. A structure or other development without the elevation certificate, other certifications, or other evidence of compliance required in the Code of Federal Regulations (CFR) §44, Sec. 60.3(b)(5), (c)(4), (c)(10), (d)(3), (e)(2), (e)(4), or (e)(5) and

corresponding parts of this ordinance is presumed to be in violation until such time as that documentation is provided.

**Watercourse** means any flowing body of water including a river, creek, stream, or a branch.

**Water surface elevation** means the height, in relation to the National Geodetic Vertical Datum (NGVD) of 1929, the North American Vertical Datum (NAVD) of 1988, (or other datum, where specified) of floods of various magnitudes and frequencies in the floodplains of coastal or riverine areas.

**Wet floodproofing** means a method of construction which allows water to enter a structure in such a way that will minimize damage to the structure and its contents. Wet floodproofing is appropriate for functionally dependent use and uses that facilitate open space use by variance only, structures utilized for parking or limited storage, or when all other techniques are not technically feasible. Wet floodproofing shall not be utilized as a method to satisfy the requirements of this ordinance for bringing substantially damaged or improved structures into compliance. Wet floodproofing is not allowed in lieu of complying with the lowest floor elevation requirements for new residential buildings.

**X Zones (shaded)** are areas of 0.2 percent chance flood that are outside of the SFHA subject to the one percent chance flood with average depths of less than one foot, or with contributing drainage area less than one square mile, and areas protected by certified levees from the base flood.

**X Zones (unshaded)** are areas determined to be outside the 0.2 percent chance floodplain.

**Zone** means a geographical area shown on a Flood Hazard Boundary Map or a Flood Insurance Rate Map that reflects the severity or type of flooding in the area.

**ARTICLE 7**  
**SEVERABILITY**

If any section, clause, sentence, or phrase of this Ordinance is held to be invalid or unconstitutional by any court of competent jurisdiction, then said holding shall in no way effect the validity of the remaining portions of this Ordinance.

Ordinance adopted on \_\_\_\_\_.

BY:

\_\_\_\_\_

Ray Long, Chairman

\_\_\_\_\_

Jeff Clark, Commissioner District 1

\_\_\_\_\_

Randy Vest, Commissioner District 2

\_\_\_\_\_

Don Stisher, Commissioner District 3

\_\_\_\_\_

Greg Abercrombie, Commissioner District 4

Certified by: \_\_\_\_\_

SEAL

Date: \_\_\_\_\_

{Page Intentionally Left Blank}